



- NOTES**
- ALL RESISTORS IN OHMS 1/2W 10% UNLESS OTHERWISE SPECIFIED
  - ALL CAPACITORS IN MFD AND 400V 10% UNLESS OTHERWISE SPECIFIED
  - D.C. VOLTAGE READINGS WITH NO SIGNAL APPLIED USING A 20,000 Ω PER VOLT VOLTMETER
  - NUMBERS IN PARENTHESIS REFER TO AMPG 5 PART NO
  - \* 2A FUSE SHOULD BE IN 240V MODELS ONLY
  - D.C. VOLTAGE READINGS ARE POSITIVE WITH RESPECT TO GROUND UNLESS OTHERWISE SPECIFIED
  - CIRCUIT OF CHASSIS MAY VARY SLIGHTLY FROM THAT SHOWN HERE DUE TO NORMAL PRODUCTION CHANGES
  - \*\* RES. 60, 61, 62, 63 & 64 ARE LOCATED ON SW1
  - \* - THE P.T. FOR 240V MODELS HAS BLCK WIRE CONNECTED TO BLUE WH. AS DOTTED LINE SHOWS

AREA CODE (971) 971-5400

LINDEN, NEW JERSEY 07036

MODEL  
B15S  
U.S. PATENT PENDING

DRN BY	DATE	DWG. NO.	PART NO.	REV.
S. C.	3-71	06400	40102580	C