



NOTES

- ALL RESISTORS IN OHMS $\frac{1}{2}$, 10% UNLESS OTHERWISE SPECIFIED.
- ALL CAPACITORS IN MFD. & 400V UNLESS OTHERWISE SPECIFIED.
- DC VOLTAGE READINGS WITH NO SIGNAL APPLIED USING A 20000 Ω PER VOLT VOLTMETER.
- NUMBERS IN PARENTHESES REFER TO AMPEGS PART NO.
- PARTS DESIGNATED BY * ARE IN 240V MODELS ONLY. THE P-1 FOR 240V MODELS HAS YUKK WIRE CONNECTED TO BLUE WIRE.
- DC VOLTAGE READINGS ARE POSITIVE WITH RESPECT TO CHASSIS GROUND UNLESS OTHERWISE SPECIFIED.
- CIRCUIT OF CHASSIS MAY VARY SLIGHTLY FROM THAT SHOWN HERE DUE TO NORMAL PRODUCTION CHANGES.
- D7-10 ARE SILICON AX TYPE 1A 400V DIODES.



POST OFFICE BOX 310
LINDEN, NEW JERSEY

MODEL
V-48

U.S. PATENT PENDING

REV. DATE: SWG. NO. PART. NO. REV.
C/W 5/71 06 700 4010267 EA