

WEERSTANDEN				CONDENSATOREN			
Benaming	Waarde	Code No.	Prijs	Benaming	Waarde	Code No.	Prijs
R1	20.000 Ohm	25.715.13		C1	6 $\mu\text{F}$		
R2 **	0.1 of 0.125 Meg. Ohm	25.722.71 of 25.722.31		C2	4 $\mu\text{F}$	25.110.24	11.50
R2 *	0.1 Meg. Ohm	72.715.05	3.50	C3	1 $\mu\text{F}$		
R3	4000 Ohm			C4	2 $\mu\text{F}$		
R4	65.000 Ohm	25.715.14		C5	1 $\mu\text{F}$		
R5	0.1 Meg. Ohm	25.717.81	1.50	C6	1 $\mu\text{F}$		
R6	1000 Ohm			C7	550 $\mu\text{M}\text{F}$	25.111.86	1.50
R7	2 Meg. Ohm	25.722.74	1.50	C8	1650 $\mu\text{M}\text{F}$	25.111.87	1.50
R8	1 Meg. Ohm	25.722.73	1.50	Combinatie C7-C8 *	als boven	25.110.29	1.50
R9	2 Meg. Ohm	25.722.74	1.50	C9 *	40 $\mu\text{M}\text{F}$	25.110.28	1.50
R10	65000 Ohm	25.715.14		C9 **	40 $\mu\text{M}\text{F}$	25.112.62	1.50
R11	10.000 Ohm	25.715.12		C10	150 $\mu\text{M}\text{F}$	25.110.01	1.50
R12	7500 Ohm	25.717.80		C11	0.5 $\mu\text{F}$	25.110.27	1.50
R13	35 Ohm	25.715.79	1.50	C12 = C15 = C32 = C33**	0.5 $\mu\text{F}$	25.112.43	3.50
R14	100.000 Ohm			C12 = C14 = C15 = C33**)	0.5 $\mu\text{F}$	25.112.43	3.50
R17	50 Ohm			C13	150 $\mu\text{M}\text{F}$	25.110.01	1.50
R18	50 Ohm			C16 **	13 $\mu\text{M}\text{F}$	25.111.38	1.50
R15	200 Ohm	25.390.05	1.50	C17 *	13 $\mu\text{M}\text{F}$	25.111.38	1.50
R16	125.000 Ohm	25.722.31	1.50	C17 ** (gecomb. met C 27)	13 $\mu\text{M}\text{F}$	25.111.42	1.50
R17-18	zie boven			C18 = C20 = C32 *	0.5 $\mu\text{F}$	25.110.25	1.50
R19	225 Ohm	25.715.80	1.50	C18 = C19 = C20 **	0.5 $\mu\text{F}$	25.110.25	1.50
R20	40.000 Ohm	25.715.94	1.50	C21 = C22 = C23	630 $\mu\text{M}\text{F}$	25.127.04	12.50
R27	30.000 Ohm						
R29	10.000 Ohm			C24 = C25 = C26	4-45 $\mu\text{M}\text{F}$		
R21	100.000 Ohm	25.722.71	1.50	C27 * (gecomb. met C17)	4 $\mu\text{F}$	25.111.42	1.50
R22	100.000 Ohm of 125.000 Ohm	25.722.71 of 25.722.31	1.50	C30	3200 $\mu\text{M}\text{F}$	25.112.61	1.50
R23	40.000 Ohm	25.715.82	1.50	C31	9000 $\mu\text{M}\text{F}$	25.110.14	1.50
R24	50.000 Ohm						
R25	40.000 Ohm			C32, C33	zie C12 etc.		
R26	50.000 Ohm						
R27	zie boven						
R28	20.000 Ohm	25.715.13	1.50				
R29	zie boven						
R30	30.000 Ohm	25.715.81	1.50				
R31	30.000 Ohm	25.715.81	1.50				

\*\*\*) Koolweerstand (in apparaten volgens schema 2511-b.)

\*) Draadweerstand (in apparaten volgens schema 2511-a.)

\*) Alleen in apparaten volgens schema 2511-a.

\*\*\*) Alleen in apparaten volgens schema 2511-b.

1) C15 en C12, 14, 33 separaat niet meer leverbaar.