



FIMI S.A. - PHONOLA - Mod. 427 trasportabile CC e CA. Una gamma onde medie da 185 a 582 m., una gamma onde corte da 21,4 a 52 m. Media frequenza 468 kc/s. Potenza indistorta 0,2 watt con alimentazione in CA. DK96: pl. 70 V, sc. 68 V, gr. oscillatrice 37 V. DF96: pl. 61 V, sc. 53 V. DAF96: pl. 20 V, sc. 18 V. DL96: pl. 82 V, sc. 85 V.

C 1	20	pf
C 2	50.000	>
C 3	1,2	>
C 4	2	Mf
C 5	90	pf
C 6	10.000	>
C 7	100	>
C 8	320	>
C 9	2500	>
C 10	250	>
C 11	3000	>
C 12	10.000	>
C 13	90	>
C 14	90	>
C 15	50	>
C 16	2000	>
C 17	10.000	>
C 18	50	>
C 19	2000	>
C 20	16	Mf
C 21	750	>
C 22	750	>
C 23	16	>
R 1	30	K Ω
R 2	2000	Ω
R 3	120	K Ω
R 4	100	Ω
R 5	30	K Ω
R 6	2	M Ω
R 7	1	M Ω
R 8	2000	Ω
R 9	70	K Ω
R 10	50	K Ω
R 11	10	M Ω