



Condensatore variabile 2CV6
RV. 0,5 MΩ log. con interr.

	1.	2.	3.	4.	5.	6.	7.
DC	●	●	○	●	●	●	○
OM.	○	○	●	○	○	○	○
F.	○	○	○	○	○	○	●

5579 B - 5579 D
5583 - 5587

L1 - L2 Bob. aereo OC - OM -
L3 - L4 > oscill. OC - OM -
L5 - L6 MF 470 KHz tipo E1 -

C	1	1000	pf.
C	2	100	
C	3	100.000	
C	4	25.000	
C	5	100	
C	6	50	
C	7	300	
C	8	200	
C	9	200	
C	10	200	
C	11	50.000	
C	12	200	
C	13	200	
C	14	100	
C	15	2000	
C	16	25.000	
C	17	200	
C	18		
C	19	10.000	
C	20	10.000	
C	21	50+50 Mf.	
C	22	10.000	pf.

R	1	150	Ω
R	2	47	K Ω
R	3	1	M Ω
R	4	47	Ω
R	5	0.47	M Ω
R	6	10	K Ω
R	7	33	K Ω
R	8	2.2	M Ω
R	9	0.1	M Ω
R	10	22	M Ω
R	11	0.1	M Ω
R	12	2.2	M Ω
R	13	0.1	M Ω
R	14	150	Ω
R	15	0.47	M Ω
R	16	1800	Ω
R	17	0.22	M Ω

PHONOLA (S. A. FIMI) - Mod. 5579B-5579D e 5583-5587.