



Condensatore variabile 2CV6

1. 2. 3. 4. 5. 6. 7.

OC. ● ● ○ ● ● ● ○
 OM. ○ ○ ● ○ ● ● ○
 F. ○ ○ ○ ○ ○ ○ ○

Verde. —
 Bianco.
 Rosso
 Nero
 IZ.619/453.

RV 0,5 MΩ log.
 RT, 0,5 MΩ log. con interr.

L1 - L2 Bob. aereo OC OM
 L3 - L4 oscill. OC - OM
 L5 - L6 MF 470 KHz

C 1	1000	pf.
C 2	100	
C 3	100.000	
C 4	100	
C 5	50	
C 6	300	
C 7	200	
C 8	200	
C 9	200	
C 10	200	
C 11	50.000	
C 12	200	
C 13	200	
C 14	200	
C 15	200	
C 16	2000	
C 17	50.000	
C 18	200	
C 19	25.000	
C 20	10.000	
C 21	5.000	
C 22	50-50 Mf.	
C 23	10.000	pf.
C 24	25 Mf.	
	5000	pf.

R 1	
R 2	47 KΩ
R 3	1 MΩ
R 4	47 Ω
R 5	
R 6	10 KΩ
R 7	33 KΩ
R 8	2,2 MΩ
R 9	47 KΩ
R 10	22 MΩ
R 11	0,1 MΩ
R 12	2,2 MΩ
R 13	0,1 MΩ
R 14	150 Ω
R 15	0,47 MΩ
R 16	1800 Ω
R 17	0,15 MΩ
R 18	0,22 MΩ
R 19	0,18 MΩ
R 20	1 MΩ

PHONOLA (S. A. FIMI) - Mod. 5584 radiofonografo.