

PHONOLA 559/A

Nomin.	Valore	Tolleranza %	Tensione di prova di Volta	Tipo		Nomin.	Valore	Toll. %	Watt
C 1	2000 pf	± 20	1500			R 1	1 M Ω	± 10	1/4
C 2	0.05 uf	± 20	1500			R 2	300 Ω	± 10	1/4
C 3	15 pf	± 10	1500	Ag.		R 3	50.000 Ω	± 10	1/4
C 4	15 pf	± 10	1500	Ag.		R 4	50.000 Ω	± 10	1/4
C 5	10 pf	± 10	1500	Ag.		R 5	50.000 Ω	± 10	1/4
C 6	0.05 uf	± 20	1500			R 6	0.1 M Ω	± 10	1/4
C 7	0.1 uf	± 20	1500			R 7	100 Ω	± 10	1/4
C 8	50 pf	± 10	1500	Ag.		R 8	1000 Ω	± 10	1/4
C 9	0.05 uf	± 20	1500			R 9	20.000 Ω	± 10	1/4
C 10	550 pf	± 10	1500	Ag.		R 10	10.000 Ω	± 10	1/4
C 11	10 pf	± 10	1500	Ag.		R 11	5000 Ω	± 10	1/4
C 12	1000 pf	± 20	1500			R 12	2 M Ω	± 10	1/4
C 13	10.000 pf	± 20	1500			R 13	50.000 Ω	± 10	1/4
C 14	5000 pf	± 20	3000			R 14	0.5 M Ω	± 10	1/4
C 15	5000 pf	± 20	3000			R 15	50.000 Ω	± 10	1/4
C 16	10.000 pf	± 20	1500			R 16	10.000 Ω	± 10	1/4
C 17	240 pf	± 20	1500	Ag.		R 17	0.1 M Ω	± 10	1/4
C 18	0.1 uf	± 20	1500			R 18	0.1 M Ω	± 10	1/4
C 19	2 pf	± 5	1500	Ag.		R 19	50.000 Ω	± 10	1/4
C 20	240 pf	± 5	1500	Ag.		R 20	2 M Ω	± 10	1/4
C 21	25.000 pf	± 20	1500			R 21	2 M Ω	± 10	1/4
C 22	25.000 pf	± 20	1500			R 22	50 Ω	± 10	1/4
C 23	8 uf	+ 30 - 20	500	G 2900		R 23	1650 Ω	± 5	Ecc. AP.
C 24	240 pf	± 20	1500	Ag.		R 24	2 M Ω	± 10	1/4
C 25	10.000 pf	± 20	1500			R 25	20.000 Ω	± 10	1/4
C 26	10 uf	+ 30 - 20	30	G 1263					
C 27	50 pf	± 10	1500	Ag.					
C 28	1 pf	± 5	1500						
C 29	100 pf	± 10	1500	Ag.					
C 30	240 pf	± 10	1500	Ag.					
C 31	100 pf	± 10	1500	Ag.					
C 32	0.05 uf	± 20	1500						
C 33	10.000 pf	± 20	1500						
C 34	25.000 pf	± 20	1500						
C 35	8 uf	+ 30 - 20	600	G 2900					
C 36	8 uf	+ 30 - 20	600	G 2900					
C 37	5000 pf	± 20	3000						

RV 1 megaohm, RT = 0,25 megaohm