

## PHONOLA 567

## CAPACITÀ

## RESISTENZE

CAPACITÀ				RESISTENZE				
Nomin.	Valore	Tolleranze %	Tensione di prova Volta	Tipo	Nomin.	Valore	Toll. %	Watt
C1	0.025 uf	±10	1500		R1	0.5 MΩ	±5	1/4
C2	0.5 uf	±10	1000		R2	2500	±5	1/4
C3	0.1 uf	±10	500		R3	10.000	±10	1/4
C4	0.1 uf	±10	500		R4	25.000	±5	1/4
C5	0.025 uf	±10	500		R5	50.000	±5	1/4
C6	0.025 uf	±10	500		R6	50	±10	1/4
C7	15 pf	±6	1500	Ag.	R7	50	±5	1/4
C8	4 pf	±20	500	Ag.	R8	200	±5	1/4
C9	0.025 uf	±10	500		R9	2000	±5	1/4
C10	0.025 uf	±10	500		R10	2500	±5	1/4
C11	100 pf	±5	1500	Ag.	R12	1 MΩ	±5	1/4
C12	0.025 uf	±10	500		R13	2 MΩ	±5	1/4
C13	100 pf	±5	1500	Ag.	R14	0.4 MΩ	±5	1/4
C14	1000 pf	±1	500	Ag.	R15	0.1 MΩ	±5	1/4
C15	1250 pf	±1	500	Ag.	R16	0.1 MΩ	±5	1/4
C16	410 pf	±5	500	Ag.	R17	0.5 MΩ	±5	1/4
C17	45 pf	±2	500	Ag.	R18	2500	±5	1/4
C18	15 pf	±2	500	Ag.	R19	1000	±5	1/4
C19	30 pf	±6	500	Ag.	R20	0.4 MΩ	±5	1/4
C20	200 pf	±3	500	Ag.	R21	20.000	±5	1/4
C21	0.025 uf	±10	500		R22	0.1 MΩ	±5	1/4
C23	200 pf	±10	1500	Ag.	R23	35	±5	1/4
C24	25 pf	±4	500	Ag.	R24	62	±5	1/4
C25	100 pf	±5	500	Ag.	R25	0.2 MΩ	±5	1/4
C26	0.025 uf	±10	500		R26	500	±10	1/4
C27	200 pf	±10	1500	Ag.	R27	1650	±5	1/4
C28	3.5 pf	±12	500		R28	1 MΩ	±5	1/4
C29	0.025 uf	±10	500		R29	250	±5	1/4
C30	200 pf	±10	1500	Ag.	R30	50	±5	1/4
C31	0.05 uf	±10	1000					
C32	25 uf	±20	15	Elettrolitico				
C33	5000 pf	±10	3000					
C34	0.1 uf	±10	1000					
C35	250 pf	±5	1500	Ag.				
C36	100 pf	±10	500					
C37	500 pf	±10	500					
C38	2000 pf	±10	500					
C39	0.5 uf	±10	1000					
C40	0.05 uf	±10	1500					
C41	500 pf	±10	1000					
C42	0.1 uf	±10	1500					
C43	1000 pf	±10	1500					
C44	1000 pf	±10	600	Elettrolitico				
C45	8 uf	±20	3000					
C46	8 uf	±20	3000					
C47	8 uf	±20	3000					
C48	2000 pf	±10	3000					
C49	5000 pf	±10	3000					

RV1 — 1MΩ esp.

RV2 — 0,5MΩ esp. Inv.

RT — 0,5MΩ esp. Inv.

Ecc. AP.