

CAPACITA'

n°	VALORI	TOLL. %	TENSIONE DI PROVA	TIPO
C 1	10000 pF	+20-10	1500 =	
C 2	200 pF	+10	1500 ~	Ag
C 3	25 pF	+5	1500 ~	Ag
C 4	412 pF	+1	1500 ~	Ag
C 5	25000 pF	+20-10	1500 =	
C 6	25000 pF	+20-10	1500 =	
C 7	2 pF	+10	1500 ~	
C 8	240 pF	-	1500 ~	Ag
C 9	240 pF	-	1500 ~	Ag
C 10	10000 pF	+20-10	1500 =	
C 11	10000 pF	+20-10	1500 =	
C 12	500 pF	+10	1500 =	
C 13	1 pF	+20-10	500 =	
C 14	10000 pF	+20-10	1500 =	
C 15	25000 pF	+20-10	3000 =	
C 16	10000 pF	+20-10	1500 =	
C 17	2 pF	+10	1500 ~	
C 18	240 pF	-	1500 ~	Ag
C 19	240 pF	-	1500 ~	Ag
C 20	200 pF	+10	1500 ~	Ag
C 21	25000 pF	+20-10	1500 =	
C 22	100 pF	+10	1500 ~	Ag
C 23	5000 pF	+20-10	1500 ~	
C 24	10000 pF	+20-10	1500 =	
C 25	1 μF	+20-10	500 =	
C 26	0.5 μF	+20-10	500 =	
C 27	5000 pF	+20-10	3000 ~	
C 28	5000 pF	+20-10	3000 ~	
C 29	8 μF	+30-20	525 =	Elett.
C 30	8 μF	+30-20	525 =	Elett.
C 31	25 μF	+30-20	30 =	Elett.

RESISTENZE

N°	VALORI	TOLL. %	WATT.
R 1	250000Ω	+ 10	1/4
R 2	50000Ω	+ 10	1/4
R 3	20000Ω	+ 10	1/4
R 4	50000Ω	+ 10	1/4
R 5	2500Ω	+ 10	1/4
R 6	250000Ω	+ 10	1/4
R 7	1MΩ	+ 10	1/4
R 8	50000Ω	+ 10	1/2
R 9	10000Ω	+ 10	1/4
R 10	2500Ω	+ 10	1/4
R 11	500000Ω	+ 10	1/4
R 12	250000Ω	+ 10	1/4
R 13	400Ω	+ 10	1/4
R 14	1MΩ	+ 10	1/4
R 15	1MΩ	+ 10	1/4
R 16	1MΩ	+ 10	1/4
R 17	2200Ω	+ 5	8
R 18	110Ω	+ 5	1
R 19	50000Ω	+ 10	1/4
R 20	250000Ω	+ 10	1/4
R 21	250000Ω	+ 10	1/4