

PHONOLA 559/F

CAPACITÀ

RESISTENZE

VALVOLE 6P7G-6A8G-6BN8G-6V6G-5Y3G MF47D Oscill. OC. OC - 470 Rc

Nomin.	Valore	Tolleranza %	Tensione di prova Volte	Tipo		Nomin.	Valore	Toll. %	Watt
C 1	2.000 pf	± 10	1500			R 1	1 M Ω	± 10	1/2
C 2	15 pf	± 10	▼	Ag.		R 2	300 Ω	± 10	1/2
C 3	15 pf	± 10	▼	Ag.		R 3	50.000 Ω	± 10	1/4
C 4	0.1 uf	± 10	▼			R 4	50.000 Ω	± 10	1
C 5	0.1 uf	± 10	▼			R 5	50.000 Ω	± 10	1/2
C 6	10.000 pf	± 10	▼			R 6	0.1 M Ω	± 10	1/2
C 7	50 pf	± 10	▼	Ag.		R 7	2 M Ω	± 10	1/2
C 8	0.05 uf	± 10	▼			R 8	2 M Ω	± 10	1/2
C 9	415 pf	± 1	▼	Ag.		R 9	200 Ω	± 10	1
C 10	1.000 pf	± 10	▼			R 10	1.000 Ω	± 10	1/2
C 11	2.000 pf	± 10	3000			R 11	2 M Ω	± 10	1/2
C 12	2.000 pf	± 10	▼			R 12	20.000 Ω	± 10	1/2
C 13	240 pf	-	1500	Ag.		R 13	5.000 Ω	± 10	1/2
C 14	1 pf	± 10	▼			R 14	5.000 Ω	± 10	2
C 15	240 pf	-	▼	Ag.		R 15	0.05 M Ω	± 10	1/4
C 16	25.000 pf	± 10	▼			R 16	0.2 M Ω	± 10	1/2
C 17	50 pf	± 10	▼	Ag.		R 17	15.000 Ω	± 10	1/4
C 18	8 uf	+ 30 - 20	500	G 2900		R 18	30.000 Ω	± 10	1/4
C 19	10.000 pf	± 10	1500			R 19	0.25 M Ω	± 10	1/4
C 20	100 pf	± 10	▼	Ag.		R 20	0.2 M Ω	± 10	1/4
C 21	10.000 pf	± 10	▼			R 21	1.000 Ω	± 10	ecc. A.P.
C 22	150 pf	± 10	▼	Ag.		R 22	50 Ω	± 10	1/2
C 23	240 pf	-	▼	Ag.		R 23	0.5 M Ω	± 10	1/4
C 24	240 pf	-	▼						
C 25	25.000 pf	± 10	▼						
C 26	10.000 pf	± 10	▼						
C 27	2.000 pf	± 10	▼						
C 28	8 uf	+ 30 - 20	500	G 2900					
C 29	8 uf	+ 30 - 20	▼	G 2900					
C 30	10 uf	+ 30 - 20	30	G 1263					
C 31	00.5 pf	± 10	1500						
C 32	10 pf	± 10	▼	Ag.					
C 33	10 pf	± 10	▼	Ag.					