

PHONOLA MOD. 715

CAPACITÀ:

C1	5 pF	C14	20 pF	C27	0,5 μ F	C40	8 μ F
C2	0,05 μ F	C15	50 pF	C28	100 pF	C41	0,25 μ F
C3	0,1 μ F	C16	2000 pF	C29	1,2 pF	C42	5000 pF
C4	5 pF	C17	5000 pF	C30	10000 pF	C43	5000 pF
C5	0,1 μ F	C18	3000 pF	C31	240 pF	C44	25 μ F
C6	0,1 μ F	C19	240 pF	C32	200 pF	C45	0,1 μ F
C7	0,1 μ F	C20	0,025 μ F	C33	100 pF	C46	0,1 μ F
C8	5 pF	C21	2 pF	C34	0,025 μ F	C47	0,1 μ F
C9	100 pF	C22	240 pF	C35	1000 pF	C48	1000 pF
C10	10 pF	C23	0,025 μ F	C36	0,025 μ F	C49	3000 pF
C11	400 pF	C24	0,1 μ F	C37	8 μ F	C50	3000 pF
C12	60 pF	C25	240 pF	C38	8 μ F		
C13		C26	10000 pF	C39	8 μ F		

RESISTENZE:

R1	0,1 M Ω	1 W	R14	0,1 M Ω	1 W	R27	1000 Ω	2 W
R2	40 K Ω	1 W	R15	1500-5000 Ω	1 W	R28	120 Ω	1 W
R3	40 K Ω	1 W	R16	50 K Ω	1 W	R29	0,5 M Ω	1 W
R4	4 M Ω	1 W	R17	50 K Ω	1 W	R30	0,5 M Ω	1 W
R5	0,1 M Ω	1 W	R18	0,5 M Ω	1 W	R31	10 K Ω	1 W
R6	20 K Ω	1 W	R19	0,5 M Ω	1 W	R32	500 Ω	1 W
R7	30 K Ω	1 W	R20	20 + 20 Ω	1 W	R33	0,1 M Ω	1 W
R8	200 Ω	1 W	R21	1 M Ω	1 W	R34	30 K Ω	1 W
R9	700 Ω	1 W	R22	2 M Ω	1 W	R35	20 K Ω	1 W
R10	40 K Ω	1 W	R23	50 K Ω	1 W	R36	20 K Ω	1 W
R11	17,5 Ω	*	R24	1100 Ω	1 W	: A filo speciale		
R12	20 K Ω	1 W	R25	400 Ω	1 W	+ Centertap		
R13	30 K Ω	1 W	R26	400 Ω	1 W	* Eccitazione altop. a 20 ^o		