

PHONOLA 910 (Telesinto)

ELENCO DELLE CAPACITÀ COMPRESSE NELLA ALTA FREQUENZA

Nomin.	Utilizzabili	Valore	Tolleranza ammessa		Tensione di prova Volt	Resistenza di isolamento	NOTE
			%	Valore Min. Valore Max			
CCCCC 1		542 pf	± 1	536.6	547.4	1500 V.	Ag
CCCCC 2		342 pf	± 1	330.6	345.4	1500 V.	Ag
CCCCC 3		0.025 uf	+ 20 - 10	0.0225	0.03	1500 V.	> 5000 MΩ
CCCCC 4		953 pf	± 1	943.5	962.5	1500 V.	Ag
CCCCC 5		1980 pf	± 2	1978	1984	1500 V.	Ag
CCCCC 6		15 pf	± 6.6	14	15	1500 V.	Ag
CCCCC 7		50 pf	± 2	49	51	1500 V.	Ag
CCCCC 8	∞	0.075 uf	+ 20 - 10	0.07425	0.0765	1000 V.	> 5000 MΩ
CCCCC 9	∞	0.075 uf	+ 20 - 10	0.07425	0.0765	1000 V.	> 5000 MΩ
CCCCC 10		~ 210 pf	-	-	-	1500 V.	Ag
CCCCC 11		0.05 uf	± 5	0.0475	0.0525	1500 V.	> 5000 MΩ
CCCCC 12		100 pf	± 10	90	110	1500 V.	Ag
CCCCC 13		0.05 uf	± 10	0.045	0.055	1500 V.	> 5000 MΩ
CCCCC 14		320 pf	± 1	316.8	323.2	1500 V.	Ag
CCCCC 15		10 pf	± 10	9	11	1500 V.	Ag
CCCCC 16		15 pf	± 6.6	14	16	1500 V.	Ag
CCCCC 17		5 pf	± 20	4	6	1000 V.	5000 MΩ
CCCCC 18		5 pf	± 20	4	6	1000 V.	5000 MΩ
CCCCC 19	∞	0.075 uf	+ 20 - 10	0.07425	0.0765	1000 V.	> 5000 MΩ
CCCCC 20	∞	0.075 uf	+ 20 - 10	0.07425	0.0765	1000 V.	> 5000 MΩ
CCCCC 21		0.05 uf	± 10	0.045	0.055	1500 V.	> 5000 MΩ
CCCCC 22		0.05 uf	± 10	0.045	0.055	1500 V.	> 5000 MΩ
CCCCC 23		320 pf	± 1	316.8	323.2	1500 V.	Ag
CCCCC 24		1000 pf	± 10	900	1100	1500 V.	> 5000 MΩ
CCCCC 25		10 pf	± 10	9	11	1500 V.	Ag
CCCCC 26		20 pf	± 5	19	21	1500 V.	Ag
CCCCC 27		5 pf	± 20	4	6	1000 V.	5000 MΩ
CCCCC 28		5 pf	± 20	4	6	1000 V.	5000 MΩ
CCCCC 29		0.02 uf	+ 20 - 10	0.018	0.024	1500 V.	> 5000 MΩ
CCCCC 30		0.02 uf	+ 20 - 10	0.018	0.024	1500 V.	> 5000 MΩ
CCCCC 31		0.02 uf	+ 20 - 10	0.018	0.024	1500 V.	> 5000 MΩ
CCCCC 32		0.02 uf	+ 20 - 10	0.018	0.024	1500 V.	> 5000 MΩ
CV 1		11-486 pf	-	-	-	1500 V.	
CV 2		11-486 pf	-	-	-	1500 V.	Vedi specifica
CV 3		11-486 pf	-	-	-	1500 V.	condensatori variabili
- 1		3-18 pf	-	-	-	1500 V.	
- 2		3-18 pf	-	-	-	1500 V.	
- 3		3-18 pf	-	-	-	1500 V.	
- 4		3-18 pf	-	-	-	1500 V.	
- 5		3-18 pf	-	-	-	1500 V.	
- 6		3-18 pf	-	-	-	1500 V.	
- 7		3-18 pf	-	-	-	1500 V.	
- 8		3-18 pf	-	-	-	1500 V.	
- 9		3-18 pf	-	-	-	1500 V.	
- 10		3-18 pf	-	-	-	1500 V.	
- 11		3-18 pf	-	-	-	1500 V.	
- 12		3-18 pf	-	-	-	1500 V.	

ELENCO DELLE CAPACITÀ COMPRESSE NELLA MEDIA FREQUENZA

CCCCC 51		~ 210 pf	-	-	-	1500 V.	Ag
CCCCC 52		0.05 uf	+ 20 - 10	0.045	0.06	1200 V.	> 5000 MΩ
CCCCC 53		0.1 uf	+ 20 - 10	0.09	0.12	1200 V.	> 5000 MΩ
CCCCC 54		0.1 uf	+ 20 - 10	0.09	0.12	1200 V.	> 5000 MΩ
CCCCC 55		~ 210 pf	-	-	-	1500 V.	Ag
CCCCC 56		0.025 uf	+ 20 - 10	0.0225	0.03	1500 V.	> 5000 MΩ
CCCCC 57		~ 210 pf	-	-	-	1500 V.	Ag
CCCCC 58		0.1 uf	+ 20 - 10	0.09	0.12	1200 V.	> 5000 MΩ
CCCCC 59		0.1 uf	+ 20 - 10	0.09	0.12	1200 V.	> 5000 MΩ
CCCCC 60		0.025 uf	+ 20 - 10	0.0225	0.03	1500 V.	> 5000 MΩ
CCCCC 61		~ 220 pf	-	-	-	1500 V.	Ag
CCCCC 62		~ 220 pf	-	-	-	1500 V.	Ag
CCCCC 63		2 pf	-	-	-	-	-
CCCCC 64		100 pf	± 10	90	110	1500 V.	Ag
CCCCC 65		100 pf	± 10	90	110	1500 V.	Ag
CCCCC 66		0.5 pf	-	-	-	-	-
CCCCC 67	⊗	0.015 uf	+ 20 - 10	0.0135	0.018	1500 V.	> 5000 MΩ
CCCCC 68	⊗	25 uf	+ 100 - 10	22.5	50	15	Ag
CCCCC 69		180 pf	± 5	171	189	1500 V.	Ag
CCCCC 70		~ 130 pf	-	-	-	1500 V.	Ag
CCCCC 71		0.01 uf	+ 20 - 10	0.009	0.012	1500 V.	> 5000 MΩ
CCCCC 72		200 pf	± 5	190	210	1500 V.	Ag
CCCCC 73		400 pf	± 2	392	408	1500 V.	Ag
CCCCC 74		500 pf	+ 30 - 10	450	575	1500 V.	> 5000 MΩ
CCCCC 75		4 uf	+ 25 - 10	3.6	5	500	Ag
CCCCC 76		0.05 uf	+ 10 - 10	0.045	0.055	1500 V.	> 5000 MΩ
CCCCC 77	X	5000 pf	+ 20 - 10	4500	5000	2000 V.	> 5000 MΩ

Vedi specifica
Trimmer